

FUJIFILM
expect INNOVATION™

HA PREMIER



HA23x7.6BE RM/RD

Technology That Inspires...

FUJINON

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101

AUDIOVIDEO SUPPLY
1-800-284-2288 sales@avsupply.com
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

HA23x7.6BE RM/RD*




Zoom Ratio / Format	23X / 2/3"
Focal Length	7.6 to 175 mm
Extender	(2X) 15.2 to 350 mm
Maximum Relative Aperture	1:1.8 (7.6 ~ 122 mm)
Aperture	1:2.65 (175 mm)
Maximum Photometric Aperture T-No.	1:1.9 (7.6 ~ 122 mm)
Aperture T-No.	1:2.8 (175 mm)
Angular Field of View	7.6 mm 64° 30' x 39° 03'
16:9 Aspect Ratio	175 mm 3° 08' x 1° 46'
	(2X) 15.2 mm 35° 01' x 19° 36'
	350 mm 1° 34' x 0° 53'
M.O.D. from Image Plane	1.07m
M.O.D. from Front of Lens	0.8m
Object Dimensions at M.O.D.	7.6 mm 952 x 535 mm
	175 mm 41 x 23 mm
	(2X) 15.2 mm 476 x 268 mm
	350 mm 21 x 12 mm
Filter Size	ø 95mm P=1 (On Barrel) / ø 107mm P=1 (In Hood)
Dia ø x Length (w/o Hood)	ø100 x 223.6 mm
Weight (w/o Hood)	1.8 kg (RM) / 1.87 kg (RD)
Options	Ratio Converter / 16 Bit Encoder
Features	Inner Focus / Zoom Limit / Quick Zoom

*RD contain servos for zoom and focus.


ACCESSORIES: HD & SD ENG/EFP

THREE-MODE FINE FOCUS

By shifting the sensitivity from the wide side to the telephoto side of the focus range, this control provides more precise focusing for studio or sports productions.



DIGI ZOOM DEMAND*



*New Digital features only available on ERM/ERD-M/S.


- A. CFC-990 Flex Cable
- B. FMM-3B/6B Manual Module
- C. ZMM-6 Manual Module
- D. EBF-1 Focus Cable
- E. MCA-6
- F. ERD-20A-A02 Zoom Demand
- G. FSP-13G Focus Positional Module
- H. EPD-4A-E02
- I. CZH-14 Focus Handle
- J. CFH-11 Focus Handle
- K. MCA-7 Mounting Clamp
- L. EPD-20A-A01/A02 Focus Demand
- M. ERD-10A-D01 Zoom Demand
- N. ALH-117A-02A Support for HA36x/A36x HA42x



Note: ERD-20A-A02 (F) and EPD-20A-A02 (L) replace the ERD-T22 and EPD-2CA.

SERIAL DIGITAL REMOTE CONTROL BY PC


Remote control of zoom, focus and iris for Digipower lenses is possible via serial digital link, providing accurate positioning for virtual studio and other applications requiring digital precision.



DIGI POWER REAR CONTROL KITS


MS-11D Manual Focus/Servo Zoom

For use with RM/ZM type lenses.




SS-11D Servo Focus/Servo Zoom

For use with RM/ZM type lenses.




SS-13D Servo Focus/Servo Zoom

For use with RD/ZD type lenses.



SS-14S Servo Focus/Servo Zoom


For use with RD/ZD type lenses.



STANDARD REAR CONTROL KITS


MS-11 Manual Focus/Servo Zoom

For use with RM/ZM type lenses.




SS-11 Servo Focus/Servo Zoom

Not available on HA42x, HA36x and A36




SS-13A Servo Focus/Servo Zoom

For use with ERD type lenses.



MM-11 Manual Focus/Manual Zoom

Not available on HA42x, HA36x and A36



*Specify camera type

**FMM-3C for use on HA36x, HA42x and HA25x


MOUNTING SYSTEM

Fujinon has replaced the "cone" shaped mounting system with the "tooth" system. The cone type may still be ordered as a special order.



ACCESSORIES: HD ENG/EFP


LENS CONVERTERS



HD/ENG LENS CONVERTERS

Model	Type	ø Size	Converter*	Mag.	Converted Focal Length (mm)	M.O.D. (m)	Weight (kg)
HS16x4.6	TELE	95 mm	TCV-H95	1.5x	74.0~111.0	0.90	1.0
	WIDE	95 mm	WCV-H95	0.8x	4.6~3.9	0.29	1.0
HS18x5.5/ HS18x5.5	TELE	85 mm	TCV-H85	1.5x	100.0~150.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	5.5~4.4	0.38	1.0
HA16x6.3	TELE	95 mm	TCV-H95	1.5x	101.0~152.0	0.90	1.0
	WIDE	95 mm	WCV-H95	0.8x	6.3~5.4	0.29	1.0
HA18x7.6E/ HA18x7.6	TELE	85 mm	TCV-H85	1.5x	137.0~205.5	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	7.6~6.1	0.38	1.0
HA18x7.6	TELE	85 mm	WAT-H85	0.7x	7.6~5.3	0.38	1.0
	WIDE	85 mm	F-ATH85	0.57x	7.6~4.3	0.26	0.6
HA22x7.3E	TELE	110 mm	TCV-H110	1.5x	161.0~242.0	1.90	1.1
	WIDE	110 mm	WCV-H110	0.8x	7.6~6.1	0.51	1.0
HA23x7.6E	TELE	100 mm	TCV-H100	1.5x	175.0~262.5	1.80	1.0
	WIDE	100 mm	WCV-H100	0.8x	7.6~6.1	0.51	1.0
XS17x5.5	TELE	85 mm	TCV-H85	1.5x	94.0~141.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	5.5~4.4	0.38	1.0
ZA17x7.6	TELE	85 mm	WAT-H85	0.7x	5.5~3.9	0.29	0.3
	WIDE	85 mm	F-ATH85	0.57x	5.5~3.1	0.19	0.3
ZA17x7.6	TELE	85 mm	TCV-H85	1.5x	130.0~195.0	1.35	1.1
	WIDE	85 mm	WCV-H85	0.8x	7.6~6.1	0.38	1.0
ZA22x7.6	TELE	100 mm	TCV-H100	1.5x	167.0~250.5	1.80	1.0
	WIDE	100 mm	WCV-H100	0.8x	7.6~6.1	0.51	1.0
ZA22x7.6	TELE	100 mm	WAT-H100	0.7x	7.6~5.3	0.39	0.5
	WIDE	100 mm	F-ATH100	0.57x	7.6~4.3	0.26	0.6

*TCV/WCV are zoom thru type **ø 95mm P-1 screw on type
Wide attachment and fisheye attachment can be used at WIDE END.
Number of M.O.D. is at wide end.



For Sales Contact Information go to
www.Fujinon.com

For design help, accessories or pricing, please contact:
sales@avsupply or call: 1-858-565-1101